

Foam Dielectric Feeder Cable Jumpers

Structure Dimension:

No.	Description*	No.	Description*
A	N/Male - N/Male	H	7/16(DIN)/Male - 7/16(DIN)/Female
B	N/Male - N/Female	I	7/16(DIN)/Female - 7/16(DIN)/Female
C	N/Female - N/Female	J	N/Male(RA) - N/Male(RA)
D	N/Male - 7/16(DIN)/Male	K	N/Male(RA) - N/Female
E	N/Male - 7/16(DIN)/Female	L	N/Male - 7/16(DIN)/Male(RA)
F	N/Female - 7/16(DIN)/Male	M	7/16(DIN)/Male(RA)-7/16(DIN)/Male(RA)
G	7/16(DIN)/Male-7/16(DIN)/Male	N	7/16(DIN)/Male(RA)-7/16(DIN)/Female



Solder Type Jumper



Clamp Type Jumper

Performance:

Item		Specification	Product Drawing
Frequency Range		0~5GHz	
Impedance		50Ω	
VSWR 10MHz-1GHz		≤1.06	
1GHz-2GHz		≤1.13	
PIM	7/16 DIN	≤ -150 ~ -158dBc	
	N	≤ -150 ~ -158dBc	
Insert Loss	Straight connector	≤0.1dB	
	Right Angle connector	≤0.15dB (RA)	
Return Loss		10MHz-1.0GHz <-28dB	
		1.0GHz-2.0GHz <-28dB	
Insulation Resistance		≥1000MΩ	
Contact Resistance	Inner Contact	≤10mΩ	
	Outer Contact	≤10mΩ	
Operating Temperature Range		-40~+85℃	
Humidity		≤95%	
Air pressure		70~106Kpa	



镇江金友电子科技有限公司

Zhenjiang Kingyou Tech. Co., Ltd

No. 1, Yuehu Rd., Jianbi Town(South Of Yanwu Bridge) Zhenjiang, Jiangsu Province, 212006 ,China

*The cable length can customize with 0.5m,1m,1.5m,2m,2.5m,3m,4m,5m,7m,10m,15m.

*The cable can customize with 1/4",1/4"SF,3/8",3/8"SF,1/2",1/2"SF,7/8",7/8"SF Feeder Cable.



JUMPERS (FOAM DIELECTRIC FEEDER COAXIAL CABLE)

Foam Dielectric Feeder Cable Jumpers

Structure Dimension:

No.	Description*	No.	Description*
1	SMA/M-SMA/M	18	BNC/M-SMA/M
2	SMA/M-SMA/F	19	BNC/M-SMA/F
3	SMA/F-SMA/M	20	BNC/F-SMA/M
4	SMA/F-SMA/F	21	BNC/F-SMA/F
5	N/M-SMA/M	22	MMCX/M-SMA/M
6	N/M-SMA/F	23	MMCX/M-SMA/F
7	N/F-SMA/M	24	MMCX/F-SMA/M
8	N/F-SMA/F	25	MMCX/F-SMA/F
9	N/Male - N/Male	26	QMA/M-SMA/M
10	N/Male - N/Female	27	QMA/M-SMA/F
11	N/Female - N/Female	28	QMA/F-SMA/M
12	N/Male - 7/16(DIN)/Male	29	QMA/F-SMA/F
13	N/Male - 7/16(DIN)/Female	30	RP-SMA/F-N/M
14	N/Female - 7/16(DIN)/Male	31	RP-SMA/F-N/F
15	7/16(DIN)/Male-7/16(DIN)/Male	32	RP-SMA/F-SMA/M
16	7/16(DIN)/Male -7/16(DIN)/Female	33	1.6/5.6/M-1.6/5.6/M
17	7/16(DIN)/Female - 7/16(DIN)/Female	34	1.6/5.6/M-1.6/5.6/F

No.	Applicable Cable	No.	Applicable Cable
1	RG141	7	RG214
2	RG142	8	RG213
3	RG174	9	RG401
4	RG179	10	RG402
5	RG316	11	
6	RG223	12	

*The cable length can customize with 0.5m,1m,1.5m,1.5m.

**COAXIAL CABLE JUMPERS**